


NOTE: WHEN ORDERING REPAIR PARTS BE SURE TO FURNISH SERIAL NUMBER & TYPE NUMBER WHICH ARE LOCATED ON NAME PLATE. ALSO PART NAME & PART NUMBER.

ITEM	DESCRIPTION	PART NO.	QTY.	
1	BASE ASSEMBLY	58866-002	1	
2	CONTACT BUSHINGS	16954-000	2	
3	ARMATURE BUSHINGS	16953-000	2	
4	STATOR ASSEMBLY	19795-000	1	
5	ARMATURE ASSEMBLY	19797-002	1	
6	ARMATURE HINGE PIN	58843-001	1	
7	#10-24 X .62 LG. PAN HEAD SEMS SCREW	49137-076	1	
8				
9	SPRING ADJUSTMENT SCREW	42899-000	1	
10				
11				
12	.312-24 HEX NUT	47253-204	1	
14	CONTACT HOLDER ARM	16927-000	1	
†15	CONTACT TIP, COPPER	17279-000	2	
††15	CONTACT TIP, SILVER TUNGSTEN	17279-003	2	
16	ARC HORN	68056-001	1	
17	.250-20 X .62 LG. S.S. HEX HEAD SCREW	47779-063	3	
18	.250 SPLIT LOCK WASHER	47252-038	4	
19	FINGER SPRING	16960-000	1	
20	MOVABLE CONTACT HINGE PIN	16968-000	1	
21	FINGER SHUNT ASSEMBLY	17408-000	1	
22	.250-20 X 1.00 LG. FILLISTER HEAD SCREW	47244-150	1	
23				
24	.250-20 HEX NUT	47253-021	1	
25	OPERATING COIL CORE	58672-001	1	
26	OPERATING COIL	SEE TABLE	1	
27	OPERATING CORE CAP	42940-000	1	
28	.312-18 X .75 FILLISTER HEAD SCREW	48624-307	1	
29	OPERATING SPRING	19257-000	1	
30	LOCKOUT COIL CORE	57658-004	1	
31				
32	.312 BRASS FLAT WASHER	47251-012	6	
33	.312-18 BRASS HEX NUT	47254-013	6	
34				
35	.312-18 X 1.75 LG. BRASS STUD	57438-042	2	
36				
37	14 GA. CL-1251 WIRE 6.00 LONG	821-141-06-14	1	
38	BLOWOUT COIL MOUNTING BASE	58667-001	1	
39	STATIONARY CONTACT BRACKET	58665-002	1	
40	BLOWOUT COIL - 230V	58860-002	SEE TABLE	1
40	BLOWOUT COIL - 550V	58860-003	SEE TABLE	1
41	BLOWOUT COIL SPACER	16971-000	1	
42	BLOWOUT GUARD	17343-000	1	
43	BLOWOUT CORE	66870-034	1	
44	BLOWOUT CORE INSULATOR	17351-000	1	
45	BLOWOUT COIL INSULATING WASHER	16961-000	2	
46	L.H. FLUX PLATE ASSEMBLY	16965-000	1	
47	R.H. FLUX PLATE ASSEMBLY	16964-000	1	
48	TERMINAL	58861-001	1	
49	.250-20 X 1.00 LG. S.S. HEX HEAD SCREW	47779-066	2	
50	.250-20 X 2.75 LG. HEX HEAD SCREW	47246-094	1	
51	.312-18 X .75 LG. HEX HEAD SCREW	47246-079	1	
52	.250-20 HEX NUT	47253-601	2	
53	.250 FLAT WASHER	47250-502	4	
54	.312 INTERNAL TOOTH LOCK WASHER	47304-010	1	
55	STANDOFF SPACER	57690-000	2	
56	.250-20 BRASS HEX NUT	47254-011	1	
57	.250 EXTERNAL TOOTH LOCK WASHER	47303-008	3	

THIS DRAWING FILE AND THE DATA SHOWN IS PROPRIETARY AND CONFIDENTIAL AND THE SOLE PROPERTY OF HUBBELL INDUSTRIAL CONTROLS. DO NOT USE OR REPRODUCE WITHOUT WRITTEN APPROVAL OF HUBBELL.

ITEM 26 OPERATING COIL		
CONTACTOR P/N	OPERATING VOLTAGE	OPERATING COIL P/N
58868-010	230/250V	68091-001
58868-011	115/125V	68091-002
58868-012	230/250V	68091-001
58868-013	115/125V	68091-002
58868-014	230/250V	68091-001
58868-015	24V	68091-003
58868-016	115/125V	68091-002
58868-017	230/250V	68091-001
58868-018	24V	68091-003
58868-019	115/125V	68091-002
58868-020	230/250V	68091-001
58868-021	24V	68091-003



△ SINGLE L.H. N.C. AUXILIARY INCLUDED IN COMPLETE CONTACTOR FOR COIL TRANSITION. ORDER ADDITIONAL AUXILIARY'S AS FOLLOWS: KIT - SINGLE BLOCK P/N 68011-004 KIT - DOUBLE BLOCK P/N 68011-005 PARTS DRG. B-68011 SHT1

ITEM	DESCRIPTION	PART NO.	QTY.
58	.250-20 X 2.00 LG. HEX HEAD SCREW	47246-071	2
59	ARC SHIELD ASSEMBLY	59694-501	1
60	AUXILIARY CONTACT ASSEMBLY, NC	68011-016	1
61	AUXILIARY CONTACT ASSEMBLY	SEE NOTE	
62	.250 S.S. SPLIT LOCK WASHER	47252-238	3
63	.312 FLAT WASHER	47250-505	1
64	ARC SHIELD RETAINER	68323-001	1
65	SPADE TERMINAL #8	57513-066	1

† CONTACT KIT 59672-007 INCLUDES COPPER CONTACT TIPS (ITEM 15), ARC HORN (ITEM 16), CONTACT SPRING (ITEM 19), AND HARDWARE (ITEMS 17 & 67).
 †† CONTACT KIT 59672-018 INCLUDES SILVER TUNGSTEN CONTACT TIPS (ITEM 15), ARC HORN (ITEM 16), CONTACT SPRING (ITEM 19), AND HARDWARE (ITEMS 17 & 67).

ITEM 40 BLOWOUT COIL	
CONTACTOR ASSEMBLY P/N	COIL P/N
58868-010, -011, -012, -015, -016, -017, -018	58860-002
58868-013, -014, -019, -020, -021	58860-003

NOTE: USE THIS RPC AFTER JULY 2012

E	D	C	B 8/8/12	REV	NEW ARC CHUTE, ECN A12-053	LINEAR	HOLE	ANGLES	R.M.S.	DATE 10-27-00	DR. T. JOHNSON/CK.	REF.
						0.X ±.050	PUNCH ±.002	DIMEN. ± 1'				
A	Rev	DATE	BY	DESCRIPTION	HUBBELL INDUSTRIAL CONTROLS, INC.	0.XX ±.020	BEAM SPECIFIED	UNDIM. 90° ±2'	50 Edwards Street Madison, Oh. 44057	1 OF 1	RPC-58868-4	1:1.75
						0.XXX ±.005						